

**Department of Transportation** 

Motor Carrier Transportation Division 3930 Fairview Industrial Drive SE Salem, OR 97302-1166 Telephone (503) 373-0000 FAX (503) 378-2873

## SPECIAL TRANSPORTATION PERMIT ATTACHMENT 82A (REVISED 03-2015)

Please read this permit carefully! This permit authorizes the movement of an oversize and/or overweight load or vehicle at the dimensions authorized on the permit and over the approved route. Corrections must be made before the movement begins. Once the permit is accepted, all permit requirements and conditions must be met. Contact (503) 373-0000 for oversize and/or overweight permits and information.

To legally operate in Oregon, tax and registration requirements must also be met unless otherwise exempt by statute or rule. This Transportation Variance Permit does not authorize your vehicle to operate in Oregon in excess of the vehicle's Registration weight or tax declared weight(s). Vehicle(s) must be registered and tax declared at the highest weight(s) appropriate to your operation. Contact ODOT MCTD Registration at (503) 378-6699 for information.

Permittee and Driver Responsibility - In accordance with OAR 734-082-0070, you are responsible and liable for any and all injury to persons or damage to property and all damage to or destruction of any highway or any highway structure resulting from the oversize or overweight movement. You are responsible for determining adequate clearance, both vertical and horizontal, for movement under this permit. It is the responsibility of the motor carrier to notify the Over-Dimension Permit Unit in the event of striking a structure in the course of a movement within 24 hours of the accident. You may be required to furnish proof of liability and property damage insurance and to file either a certified check or a surety bond as deemed necessary. You are also responsible for contacting public utilities (i.e. telephone, electric, cable, etc.) to determine oversize load clearance.

The driver is responsible for complying with all applicable Oregon laws in addition to all permit requirements and provisions. It is the driver's responsibility to determine if local road conditions are hazardous, unless the Department of Transportation has closed or posted signs on the highway displaying restrictions due to weather/road conditions in the area. In such cases the permitted vehicle must leave the highway at the next available exit, truck stop, rest area, or next available safe parking place and shall not proceed until the hazardous condition abates. Drivers making the wrong choice and continuing to operate when hazardous conditions exist, or who violate any other permit requirement or provision, are subject to citation. In addition, the responsible Motor Carrier is subject to civil monetary complaint on a first offense; and in the instance of repeated violations, is subject to additional sanctions including cancellation of permit and/or denial of future permit requests.

Drivers must enter an Oregon scale when directed to do so by an open sign. If the vehicle is equipped with a transponder and you are transporting an oversize/overweight vehicle or load, you must enter the open scale regardless of receiving a green light.

This permit is not valid for vehicles licensed, or which can be used as recreational vehicles as defined by ORS 446.003(33), unless specifically authorized on the permit. This permit is not valid for any combination of more than two vehicles not used exclusively for commercial purposes and subject to ORS Chapters 823 and 825.

This is a brief summary of regulations governing the transportation of non-divisible loads and/or vehicles. For a complete copy of Oregon Administrative Rule, Chapter 734, Division 82, contact us at the address shown on this attachment or at our Website: www.oregontruckingonline.com.

This permit is valid for the time period specified on the permit. Single trip permits (STPs) are valid for a single move and shall not exceed ten days. Continuous trip permits (CTPs) are valid for multiple trips within the time frame specified on the permit not to exceed one year. The department may cancel a permit if the permit holder violates any permit terms or conditions, obtains it improperly, or if public interest requires cancellation.

Single trip permits will propose a suggested route that must be followed in the sequence shown on the permit. Actual operation under the authority of a single trip permit will establish that the Permittee has verified the adequacy of the suggested route. Therefore, it is required that the Permittee contact the Over-Dimension Permit Unit to request changes deemed necessary to the suggested route prior to actual operation. The Permittee assumes all liability for any damages resulting from operations under the permit. Continuous trip permits generally are accompanied by route maps displaying routes authorized by the permit. On occasion, some continuous trip permits are route specific and require travel in the sequence suggested on the permit. In those instances it will similarly be required that the Permittee contact the Over-Dimension Permit Unit prior to operation if the suggested route is deemed inadequate. Operation under the permit means the Permittee confirms the suggested route is appropriate and the Permittee assumes all liability for any damages resulting from operations under the permit.

Attachment 82A, Page 1 of 4 FORM 734-1994 (3-15) STK# 202235

Legal height in Oregon is 14 feet 0 inches and legal width is 8 feet 6 inches. This permit is not valid for oversize caused by items loaded side by side or overlapping, items stacked one on top of another, or loaded end to end, unless specifically authorized on the permit. This permit is not valid for weight in excess of that allowed by ORS 818.010 when items are loaded in multiple unless specifically authorized on the permit. When the hauling equipment exceeds 8 feet 6 inches in width, the load must be non-divisible in width unless specifically authorized on the permit. A semitrailer shall not exceed 53 feet in length, unless authorized on the permit.

This permit does not authorize county roads and city streets unless specifically stated on the permit. To operate over these roads or

This permit does not authorize county roads and city streets unless specifically stated on the permit. To operate over these roads or streets, a permit must be obtained from the appropriate county or city. The Salem permit office can obtain approval for single trip permits in most counties. Such approval is noted under Special Provisions on the permit.

**Highways or structures may be posted to reduce size or weight limits.** Drivers shall not exceed posted load limits regardless of the weights or sizes authorized by this permit.

This permit does not authorize the use of detour routes unless your permit specifically allows the use of the route at the size and weight of your load and vehicle(s). Detour routes are temporary routes that are established primarily for legal size and legal weight vehicles. You must contact a permit agent and obtain a new permit before continuing your move.

#### Refer to separate Attachment H for Hauling Hours and Days for Overwidth Movement.

Weather Restrictions: Movement of a vehicle or combination of vehicles exceeding 8 feet 6 inches in width is prohibited:

- When road surfaces are hazardous due to ice, snow or frost; or
- When visibility is less than 500 feet due to snow, mist, rain, dust, smoke, fog or other atmospheric conditions; or
- When wind conditions exist which cause excessive swaying or weaving, or tip-over of the towed unit, or are such that the towed unit cannot maintain its lane of travel: or
- When the Department of Transportation places signs indicating travel is hazardous.

Note: Chain up locations are not intended to serve as staging areas for over dimension vehicles. Parking in chain-up areas is strictly prohibited. In order to avoid being caught unaware of existing or approaching weather conditions ALWAYS check for available highway and weather information before beginning a trip.

Prior to travel, go to <u>www.tripcheck.com</u> or call the toll free Oregon road report at 511 or (800) 977-6368 for current travel and weather information throughout Oregon. If calling from out of state, call (503) 588-2941.

Warning Signs: Vehicle(s) transporting a load that exceeds 8 feet 6 inches in width or 80 feet in length are required to display standard signs bearing the words "OVERSIZE LOAD\*." The signs must be displayed at the front and rear of the solo vehicle or the combination of vehicles.

\*Warning signs for vehicles or loads that exceed 8 feet 6 inches in width and are 80 feet or less in overall length, inclusive of load, may bear the words "WIDE LOAD." Signs for vehicles or loads that do not exceed 8 feet 6 inches in width may bear the words "LONG LOAD" when the overall length, inclusive of load, exceeds 80 feet. Signs must meet the standards described in OAR Chapter 734 Division 82.

- Signs must be 7 feet wide by 18 inches high with black letters 10 inches high with 1-5/8 inch brush stroke in accordance with Federal Highway Administration series C on highway yellow background.
- The highway yellow background of the sign shall be made of reflectorized material when operating between one half-hour after sunset and one half hour before sunrise.
- When three front pilot vehicles are required by a permit, additional signs that bear the legend "REDUCE SPEED" and "MOVE RIGHT" may be required. These signs shall be at least five feet wide by ten inches high; have black letters eight inches high with one-inch brush stroke in accordance with Federal Highway Administration series B, on highway yellow background.
- Signs must be kept in good repair, free from dirt, grease and road film, and be clearly readable to other drivers. The signs shall not cover or interfere with the visibility of the registration plate. To meet this requirement, plates may be mounted to cover a portion of the sign's background, as long as the sign's legend remains readable.
- If placement of the signs described above on a self-propelled mobile crane obscures the vehicle's headlights, turn signals, license plates, brake lights or taillights, the requirements may be met if the vehicle's front and rear bumpers are constructed or painted with a highway yellow background and the words "OVERSIZE LOAD" are painted, or applied by decal, on the bumper. Visibility of the sign may not be obscured by any other part of the vehicle, including but not limited to an auxiliary axle or jeep axle. All other sign requirements above apply.

**Spacing Interval -** The convoy movement of two or more vehicles required to display oversize, long load or wide load signs is strictly prohibited, unless specifically authorized on the permit. All slow-moving lanes and turnouts must be used to allow following traffic to pass. Except when overtaking or passing, a distance of one-half mile shall be maintained between combinations traveling in the same direction.

**Rearview Mirrors** - A power unit must be equipped with a minimum of two rear view mirrors positioned to allow the operator to view the rear of the last vehicle of the combination and to see down each side of the vehicle(s) being transported. Mirrors may exceed authorized width only as much as required to provide the operator the required view to the rear and must be retracted to legal width at all other times.

Attachment 82A, Page 2 of 4 FORM 734-1994 (3-15) STK# 202235

#### Warning lights for power units when the width exceeds 8 feet 6 inches:

- In addition to any other lights required by law, an overwidth motor vehicle or a vehicle transporting an overwidth load shall be equipped with amber warning lights when the width exceeds 10 feet on a 2-lane or 12 feet on a multi lane highway.
- These lights shall be mounted above the roof of the cab, be clearly visible from a distance of 500 feet, have a minimum of 30 flashes per minute and be either:
  - (A) Two flashing amber lights as widely spaced laterally as is practical;
  - (B) Revolving type amber light(s); or
  - (C) Amber type strobe light(s) with 360 degree visibility.
- An overwidth vehicle or a vehicle transporting an overwidth load is exempt from the warning light requirements when operating with a minimum of two pilot vehicles on all highways.

#### Red/Fluorescent Orange flags and lights to mark extremities:

- Overwidth loads must be marked at the outermost extremities during daylight hours with red/fluorescent orange flags not less than 18 inches square, visible to the front and rear. The attachment device shall not extend beyond the widest extremity by more than 3 inches on either side. During the hours of darkness the outermost extremities must be illuminated by lamps or markers as described by the requirements of ORS Chapter 816.
- Loads extending beyond the rear of the load-carrying part of the vehicle 4 feet or more, shall be visibly marked with a red/fluorescent orange flag not less than 18 inches square attached to the outermost extremity of the load during daylight hours. The attachment device shall not extend beyond the rear of the load more than 3 inches. End load lights described in ORS 816.290 are required when visibility is less than 500 feet due to darkness, snow, mist, rain, dust, smoke, fog or other atmospheric conditions when a load extends beyond the rear of the load carrying part of the vehicle 4 feet or more.

Loads transported on drop deck trailers: When a load more than 40 feet in length extends more than 5 feet beyond the rear of the semitrailer, the load must be non-divisible in length and the length of the load must be specified on the permit. The load may be transported on the lower deck of a drop deck semitrailer and may extend beyond the rear of the trailer up to the length authorized by the permit. In addition to the load transported on the lower deck of a drop deck trailer, a load may be transported on the upper deck of the trailer providing the load does not exceed 14 feet in height or the height authorized by the permit. When an over-dimension permit authorizes a height exceeding 14 feet, the load on the upper deck may not exceed the height of the load on the lower deck, and must be non-divisible in height. When a divisible load is transported on the upper deck and the lower deck of a drop deck trailer, the weight shall not exceed Permit Weight Table 1 or 2 as authorized by the permit.

#### Weights authorized by permit are subject to all the following limits:

- Tires may carry up to 600 pounds per inch of tire width or the manufactured sidewall rating, whichever is less.
- Permits issued for divisible loads or non divisible load authorizing Permit Weight Tables 1 or 2 allow up to a maximum of 20,000 pounds on a single axle and 34,000 pounds on a tandem axle; and authorizes Exceptions 1 and 2 shown on Permit Weight Table 1.
- Permits issued for a non-divisible load authorizing Permit Weight Tables 3 and 4 allow up to a maximum of 21,500 pounds per single axle and up to 43,000 pounds per tandem axle. Permits issued for a non-divisible load authorizing Permit Weight Table 5 allow up to a maximum of 24,000 lbs. per single axle, 48,000 lbs. per tandem axle when the combination consists of a steering axle and four or more consecutive tandem axles. When additional axle weights are authorized by permit, axle weights must be specified on the permit.
- Permits issued for non-divisible self-propelled or towed fixed load vehicles equipped with low pressure flotation tires at least 15 inches wide are authorized up to 700 pounds per inch of tire width up to a maximum of 36,000 pounds on a single axle and 43,000 pounds on a tandem axle.
- All groups of axle weights shall not exceed the sums of the permittable axle weights or the weights allowed by the Permit Weight Table whichever is the lesser of the two. When the permit authorizes a Permit Weight Table Formula, the formula shall take precedence over the weight specified on a permit weight table.
- Combined gross weight shall not exceed that specified on the permit.
- Auxiliary axle(s) must be deployed, and distribute the weight of the load or vehicle, when failure to do so results in any tire, axle, tandem axle or group of axles exceeding the weight limits allowed by OAR 734-074-0020.

When transporting a single non-divisible load and the combined gross weight of the vehicle/load exceeds 98,000 pounds, a Single Trip Permit must be obtained and Road Use Assessment Fees paid in lieu of weight-mile taxes.

"Heavy Haul" is a term used to denote weight(s) for non-divisible loads that exceed those authorized by Permit Weight Table 1 and Permit Weight Table 2.

**Specifically identified locations may require additional precautions**. Permits may specify locations that require certified flagging to be conducted. The flagging shall be conducted in accordance with the standards in the Manual on Uniform Traffic Control Devices as adopted in OAR 734-020-0005. In accordance with OAR 734-070-0060, Pilot Vehicle operators certified in traffic control may direct traffic when the variance permit authorizes a rolling stop option in lieu of certified flagging. The rolling stop method shall be conducted with three pilot vehicles that are certified and trained to perform the rolling stop method.

Pilot vehicles may be required to ensure safety during the movement of oversize loads. A pilot vehicle may <u>not</u> tow another vehicle. The pilot vehicle(s) shall be positioned at a distance of 300 feet to 500 feet from the oversize vehicle/load. In areas where traffic congestion is

Attachment 82A, Page 3 of 4 FORM 734-1994 (3-15) STK# 202235

encountered, where traffic is controlled by signals, or where other conditions may require, the spacing shall be reduced as may be required to properly safeguard the traveling public. Pilot vehicles are under direct supervision of the operator of the vehicle to which the permit is issued. **Two-way radio communications** between the oversize vehicle and the pilot vehicle(s) must be maintained at all times.

#### Pilot vehicles escorting oversize loads or vehicles are required to have the following equipment:

- Warning signs mounted above the roofline. The sign shall be at least 5 feet wide by 10 inches high; have black letters 8 inches high with 1 inch brush stroke in accordance with Federal Highway Administration series B, on highway yellow background.
- Each pilot vehicle operator shall use warning flags to warn oncoming or overtaking traffic when the oversize unit is stopped and obstructing traffic. Warning flags shall be two 18 inches square red/fluorescent orange flags mounted on 3 feet length staffs.
- In addition, eight safety flares or reflectors shall be carried in each pilot vehicle.
- \*\*When height exceeds 14 feet 06 inches a front pilot vehicle is required, unless the permittee has filed a declaration with MCTD assuming complete and total liability for any and all injury and damage that may result from the overheight movement. When required, the front pilot vehicle must be equipped with a height pole that is constructed of material that is non-conductive and non-destructive to overhead structures and which measures as high as the load being transported. The pilot vehicle must slow and have the height pole deployed when crossing under a structure to allow time for the load to stop if the height pole strikes the structure. In an instance that the height pole strikes a structure the pilot car must radio to the oversize vehicle instructions to pull over and cease movement. The driver of the oversize vehicle shall call OD Permits at (503) 373-0000 immediately to obtain further routing advice. When not required, the height pole must be down and secured to the pilot vehicle.

**Pilot vehicles must have warning lights** in addition to those lights that may otherwise be required by law. Warning lights shall be displayed only during the course of the oversize movement, and at all other times the requirements found in ORS 816.350(7) shall apply. These lights shall be mounted above the roof of the cab, be clearly visible from a distance of 500 feet, have a minimum of 30 flashes per minute and be either: Two flashing amber lights as widely spaced laterally as is practical; revolving type amber light(s); or amber type strobe light(s) with 360 degree visibility.

#### Pilot Vehicles -

- When one pilot vehicle is required for width, it shall travel in front of the oversize unit except when operating on multilane highways it shall be at the rear of the unit. When two pilot vehicles are required, one shall be in front and one shall be at the rear of the oversize unit.
- When a pilot vehicle is required for height, it shall travel in the front.
- When the number of pilot vehicles specified on the permit is different than the number required below, the permit shall take
  precedence.

precedence.	Annual Company of the Annual Annual Company of the Annual	MIN	IMUM I	PILOT V	EHICLE	S REQU	IRED FOR WII	TH		
OPERATIONS	INTERSTAT	E AND	ROUTE	MAP 2	ROUTE	MAP 2	ROUTE M	MAP 2 RED ROUTES – SEE GROUP MAP 1		
EXCEEDING 8'6" IN WIDTH	MULTIL HIGHWA		GREEN	ROUTES	PURPLE	ROUTES	GROUP MAP BLACK ROUT		P MAP 1 ROUTES	GROUP MAP 1 RED ROUTES
08'07" to 09'	NON	E	NO	NE	NC	NE	NONE	О	NE	TWO
09'01" to 10'	NON	Ε	NO	NE	O	NE .	ONE	0	NE	TWO
10'01" to 11'	NON	E	NO	NE	O	NE	ONE	О	NE	TWO
11'01" to 12'	NONI	E	NO	NE	O	NE	TWO	T	wo	TWO
12'01" to 14'	NONI	E	Ol	NE	TV	vo	TWO	T	wo	TWO
14'01" to 16'	ONE in R	EAR	TV	vo	TV	vo	TWO	T	wo	TWO
Over 16'		Specified by Specified by SPermit Permit			ied by mit	Specified by Permit		fied by rmit	Specified by Permit	
	<u> </u>	MINI	MUM P	LOT VI	EHICLES	REQUI	RED FOR LEN	GTH		
OVERALL LENG EXCEEDING 95'		,	INTER Multila	STATE AN		ROUTE MAP 2 2 LANE GREEN ROUTES		ALI	ALL OTHER 2-LANE HIGHWAYS	
95' 01" to 110	<del> </del>			ONE	WAID	NONE			ONE	
110'01" to 120				ONE			ONE			ONE
120'01" to 150	D'		ONE	in REAJ	R		TWO		TWO	
Over 150'			Specifie	d by Per	mit	Specified by Permit Specif		cified by Permit		
	MIN	NIMUM	PILOT	VEHICI	LES REQ	UIRED F	OR FRONT O	ERHANG		
FRONT OVERHA				INTERS	FATE AND	MULTILA	NE HIGHWAYS	AL	L 2-LANE I	HIGHWAYS
	BEYOND THE FRONT BUMPER OR			NONE ONE in FRONT		RONT				
FOREMOST PAR	FOREMOST PART OF THE VEHICLE MINIMUM DILOT VEHIC			EHICLES	REOU	RED FOR HEI	CHT			
MINIMUM PILOT VEHICLES REQUIRED FOR HEIGHT										
Overall Height exceeding 14'00"				All Interstate/Multilane & 2 Lane Highways None						
14'01" to 14'06"						_	1 to the	***		
Over 14'06" One in Front**				e in Fron						



**Department of Transportation** Motor Carrier Transportation Division 3930 Fairview Industrial Drive SE

Salem, OR 97302-1166 Telephone (503) 373-0000 FAX (503) 378-2873

#### SPECIAL TRANSPORTATION PERMIT ATTACHMENT H (Revised 03-2015)

Time of travel restrictions for overwidth loads are shown in the tables below. These tables are applicable to all overwidth movement authorized by either Annual or Single Trip Permits that also require Attachments 70A, 75A, or 82A. "Daylight hours" means one-half hour before sunrise until one-half hour after sunset.

Hours of Darkness (1/2 hour after sunset to 1/2 hour before sunrise)

Width	All Interstates	Green Routes on Route Map 2	All other routes
8'7"-10'0"	Allowed	Allowed	Not Allowed
10'1" to 12'0"	Allowed**	Not Allowed	Not Allowed
More than 12'0"	Not Allowed	Not Allowed	Not Allowed

<sup>\*\*</sup> Manufactured homes / Modular units are limited to 10 feet in width on the Interstate Highways during hours of darkness.

When operating during hours of darkness, the outermost extremities must be illuminated by lamps/markers described in ORS Chapter 816. Lighting requirements so described in ORS Chapter 816 and in FMCSR Chapter 393 apply before sunrise and after sunset.

#### Urban Areas (Portland, Salem, Eugene, Grants Pass, Medford)

Movement between 7 AM to 9 AM, and 4 PM to 6 PM (City Hours, Business Days)

Width	I-5 between WA & OR217	I-5 Exit 24-33	All Other Interstates	All Non-Interstates
8'7"-12'0"	Allowed	Allowed	Allowed	Allowed
12'1" to 14'0"	Not Allowed	Not Allowed	Allowed	Not Allowed
More than 14'0"	Not Allowed	Not Allowed	Not Allowed	Not Allowed

Travel time restrictions are for both directions of travel.

In addition, no movement between 11 AM and 1 PM in Portland, Salem, Eugene, Grants Pass, and Medford Urban Areas, on all highways, when more than 14'0" wide (for mobile / modular units, more that 14'0" base width, or more than 15'0" overall width).

#### **Additional Portland Area restrictions**

Movement between 7 AM to 9 AM, and 4 PM to 6 PM Monday through Friday

Width	I-5 between WA & MP278	I-84 between MP15 & I-5	I-205	US26 (Sunset) between MP64 & I-405	
More than 14'0" ***	Not Allowed	Not Allowed	Not Allowed	Not Allowed	
*** for mobile / modu	** for mobile / modular units, more than a 14'0" base width, or more than 15'0" overall width.				

Travel time restrictions are for both directions of travel.

Summertime Weekend Davlight Hours (after 12 noon on Saturday, and all day Sunday)

	COMMENTAL CRAME III	CIRCIAC INC. JAILOU ILOUIN (MILES		
	Width	All Interstates	Non-interstates west of Cascades	Authorized routes east of Cascades *
	8'7" to 14'0"	Allowed	Not Allowed	Allowed
-	more than 14'0"	Not Allowed	Not Allowed	Not Allowed

<sup>\*</sup> Authorized routes are any route allowed on a single trip, continuous trip, or annual permit.

Summertime weekends are from the last Monday in May to the first Monday in September, not including holiday weekends (Memorial Day, Labor Day, Independence Day if applicable)

Attachment H Page 1 of 2

FORM 734-2362 (3-15) STK# 320542

#### Holiday: New Year's Day, Memorial Day, Independence Day, Labor Day, Christmas Day

When holiday is observed on a Monday

Width	Noon Friday to 12:01am Saturday	12:01am Saturday to midnight Sunday	Monday	12:01am Tuesday to 1/2 hr before sunrise
8'7"-14'0"	Not Allowed	Allowed on authorized routes * **	Not Allowed	Allowed on authorized routes **
more than 14'0"	Not Allowed	Not Allowed	Not Allowed	Not Allowed

When holiday is observed on a Tuesday

	y 15 05001 (th 01 th 1 th 05th)	
Width	Noon Monday to 12:01am Wednesday	12:01am Wednesday to 1/2 hr before sunrise
8'7"-14'0"	Not Allowed	Allowed on authorized routes **
more than 14'0"	Not Allowed	Not Allowed

When holiday is observed on a Wednesday

	<u> </u>	
Width	Noon Tuesday to 12:01am Thursday	12:01am Thursday to 1/2 hr before sunrise
8'7"-14'0"	Not Allowed	Allowed on authorized routes **
more than 14'0"	Not Allowed	Not Allowed

When holiday is observed on a Thursday

Width	Noon Wednesday to 12:01am Friday	12:01am Friday to 1/2 hr before sunrise
8'7"-14'0"	Not Allowed	Allowed on authorized routes **
more than 14'0"	Not Allowed	Not Allowed

When holiday is observed on a Friday

Width	Noon Thursday to 12:01am Friday	12:01am Friday to midnight Saturday	Sunday	12:01am Monday to 1/2 hr before sunrise
8'7"-14'0"	Not Allowed	Allowed on authorized routes * **	Not Allowed	Allowed on authorized routes **
more than 14'0"	Not Allowed	Not Allowed	Not Allowed	Not Allowed

Holiday: Thanksgiving

Width	Noon Wednesday to 12:01am Thursday	12:01am Thursday to midnight Saturday	Sunday	12:01am Monday to 1/2 hr before sunrise
8'7"-14'0"	Not Allowed	Allowed on authorized routes * **	Not Allowed	Allowed on authorized routes **
more than 14'0"	Not Allowed	Not Allowed	Not Allowed	Not Allowed

<sup>\*</sup> Authorized routes during daylight hours are any Interstate, US97, and black routes on Map 6 or 9 east of US97.

Observed Holidays that are not travel restricted in Oregon:

Martin Luther King, Jr. Day (January)
 President's Day (February)

• Veteran's Day (November)

Attachment H Page 2 of 2

<sup>\*\*</sup> See Hours of Darkness chart for authorized routes during hours of darkness (1/2 hour after sunset to 1/2 hour before sunrise).



35 feet or more

### **Permit Weight Table 1**

(REVISED 03-2014)

The following exceptions apply to the table of weights shown below:

Exception 1: Two consecutive tandem axles may weigh up to 34,000 pounds each if:				
Minimum Axle Spacing Required	Interstate Highways	Non-Interstate Highways		
30 feet or more	Permit Required	No Permit Required		
36 feet or more	No Permit Required	No Permit Required		

A group of four axles consisting of a set of tandem axles and two axles spaced nine feet or more apart may have a loaded weight of more than 65,500 pounds and up to 70,000 pounds if:

Minimum Axle Spacing Required Interstate Highways Non-Interstate Highways

Permit Required

No Permit Required

Minimum axle spacing is the distance between the first and last axle of any group shown above.

Wheelbase			Number	of Axles			Wheelbase	Number of Axles								
In Feet *  ▼	2	3	4	5	6	7 Or More	In Feet *	2	3	4	5	6	7 Or More			
4	34,000	34,000	34,000	34,000	34,000	34,000	31	40,000	59,000	62,500	67,500	72,500	78,000			
5	34,000	34,000	34,000	34,000	34,000	34,000	32	40,000	60,000	63,500	68,000	73,000	78,500			
6	34,000	34,000	34,000	34,000	34,000	34,000	33	40,000	60,000	64,000	68,500	74,000	79,000			
7	34,000	34,000	34,000	34,000	34,000	34,000	34	40,000	60,000	64,500	69,000	74,500	80,000			
8 & less	34,000	34,000	34,000	34,000	34,000	34,000	35	40,000	60,000	65,500	70,000	75,000	80,000			
Over 8	38,000	42,000	42,000	42,000	42,000	42,000	36	40,000	60,000	66,000	70,500	75,500	80,000			
9	39,000	42,500	42,500	42,500	42,500	42,500	37	40,000	60,000	66,500	71,000	76,000	80,000			
10	40,000	43,500	43,500	43,500	43,500	43,500	38	40,000	60,000	67,500	71,500	77,000	80,000			
11	40,000	44,000	44,000	44,000	44,000	44,000	39	40,000	60,000	68,000	72,500	77,500	80,000			
12	40,000	45,000	50,000	50,000	50,000	50,000	40	40,000	60,000	68,500	73,000	78,000	80,000			
13	40,000	45,500	50,500	50,500	50,500	50,500	41	40,000	60,000	69,500	73,500	78,500	80,000			
14	40,000	46,500	51,500	51,500	51,500	51,500	42	40,000	60,000	70,000	74,000	79,000	80,000			
15	40,000	47,000	52,000	52,000	52,000	52,000	43	40,000	60,000	70,500	75,000	80,000	80,000			
16	40,000	48,000	52,500	58,000	58,000	58,000	44	40,000	60,000	71,500	75,500	80,000	80,000			
17	40,000	48,500	53,500	58,500	58,500	58,500	45	40,000	60,000	72,000	76,000	80,000	80,000			
18	40,000	49,500	54,000	59,000	59,000	59,000	46	40,000	60,000	72,500	76,500	80,000	80,000			
19	40,000	50,000	54,500	60,000	60,000	60,000	47	40,000	60,000	73,500	77,500	80,000	80,000			
20	40,000	51,000	55,500	60,500	66,000	66,000	48	40,000	60,000	74,000	78,000	80,000	80,000			
21	40,000	51,500	56,000	61,000	66,500	66,500	49	40,000	60,000	74,500	78,500	80,000	80,000			
22	40,000	52,500	56,500	61,500	67,000	67,000	50	40,000	60,000	75,500	79,000	80,000	80,000			
23	40,000	53,000	57,500	62,500	68,000	68,000	51	40,000	60,000	76,000	80,000	80,000	80,000			
24	40,000	54,000	58,000	63,000	68,500	74,000	52	40,000	60,000	76,500	80,000	80,000	80,000			
25	40,000	54,500	58,500	63,500	69,000	74,500	53	40,000	60,000	77,500	80,000	80,000	80,000			
26	40,000	55,500	59,500	64,000	69,500	75,000	54	40,000	60,000	78,000	80,000	80,000	80,000			
27	40,000	56,000	60,000	65,000	70,000	75,500	55	40,000	60,000	78,500	80,000	80,000	80,000			
28	40,000	57,000	60,500	65,500	71,000	76,500	56	40,000	60,000	79,500	80,000	80,000	80,000			
29	40,000	57,500	61,500	66,000	71,500	77,000	57 or	40,000	60,000	80,000	80,000	80,000	80,000			
30	40,000	58,500	62,000	66,500	72,000	77,500	more	L								

The loaded weight of any group of axles, vehicle, or combination of vehicles shall not exceed that specified in the table of weights shown above or any of the following:

- The manufacturer's side wall tire rating but not to exceed 600 pounds per inch of tire width.
- 600 pounds per inch of tire width.
- 20,000 pounds on any one axle, including any one axle of a group of axles.
- 34,000 pounds on any tandem axle.
- The sum of the permittable axle, tandem axle, or group of axle weights shown above, whichever is less.

Note exceptions 1 and 2 above.

# PERMIT WEIGHT TABLE 2

	WHEELBASE ]					
	·	5 Axles	6 Axles	7 Axles	8 or More Axles	
	47	77500	81000	81000	81000	
	48	78000	82000	82000	82000	
	49	78500	83000	83000	83000	
	50	79000	84000	84000	84000	
	51	80000	84500	85000	85000	
٠	52	80500	85000	86000	86000	
	53	81000	86000	87000	87000	
•	54	81500	86500	88000	91000	
	55	82500	87000	89000	92000	
•	56	83000	87500	90000	93000	
	57	83500	88000	91000	94000	
	58	84000	89000	92000	95000	
	59	85000	89500	93000	96000	
	60	85500	90000	94000	97000	
	61	86000	90500	95000	98000	
	62	87000	91000	96000	99000	
	63	87500	92000	97000	100000	
·	64	88000	92500	97500	101000	
	65	88500	93000	98000	102000	
	66	89000	93500	98500	103000	
	67	90000	94000	99000	104000	
	68	90000	95000	99500	105000	
	69	90000	95500	100000	105500	
	70	90000	96000	101000	105500	and the same of th
	71	90000	96500	101500	105500	
	72	90000	96500	102000	105500	
• .	73	90000	96500	102500	105500	
	74	90000	96500	103000	105500	
	75	90000	96500	104000	105500	
	76	90000	96500	104500	105500	
·	77	90000	96500	105000	105500	
	78	90000	96500	105500	105500	

See Weight Table 1, if using less than five axles or 47 feet wheelbase.



OREGON DEPARTMENT OF TRANSPORTATION MOTOR CARRIER TRANSPORTATION DIVISION TRANSPORTATION PERMIT UNIT 3930 FAIRVIEW INDUSTRIAL DRIVE SE SALEM OREGON 97302-1166

## Permit Weight Table 3 REVISED 03-2014

WHEEL BASE 4	2 Axies 43,000	3 Axles	4 Axies	5 Axles	6 Axies	7 Axles	8 Axles	9 Axles	10 Axles	11 Axles or more
5	43,000 43,000	Colores .								
7 8	43,000 43,000									
OVER 8' (B	UT LESS THA 43,000	N 8'6") 48,000			The load	ad weight o	f a group of	avles vehi	cles or con	nhination
9 10	43,000 43,000	49,000 <b>50,000</b>			of vehicle	s shall not i	exceed that			
11 12	43,000 43,000	51,000 <b>52,000</b>			table or a	ny of the fo	llowing:		10000	
13 14	43,000 43,000	53,000 <b>54,000</b>					ıcturer's sid			t to
15 16	43,000 43,000	55,000 <b>56,000</b>					pounds pei nds per sing		width;	
17 18	43,000 <b>43,00</b> 0	57,000 <b>58,000</b>			7	<b>13,000</b> pour	nds per tand	dem axle;		
19 20	43,000 43,000	64,500 <b>64,500</b>	70,800 <b>72,000</b>				shown on th the permitta			or group
21 <b>22</b>	43,000 <b>43,00</b> 0	64,500 64,500	73,200 <b>74,400</b>	1	ı	axle weight,	whichever	is less;		
23 24	43,000 <b>43,000</b>	64,500 64,500	75,600 <b>76,800</b>		(	Or except a	s described	in OAR 73	4-082-0010	(2)
25 26	43,000 43,000	64,500 <b>64,500</b>	78,000 78,000 <b>79,200</b>	Se .						
27 28	43,000 43,000 43,000	64,500 64,500	80,400 81,600							
29 30	43,000 43,000	64,500 64,500	82,800 <b>84,000</b>	*						
31 32	43,000 43,000	64,500 <b>64,500</b>	85,200 86,000	86,400						
33 34	43,000 43,000	64,500 64,500	86,000 86,000	87,600 88.800						
35 36	43,000 <b>43,</b> 000	64,500 64,500	86,000 86,000	90,000 91,200						
37 38	43,000 43,000	64,500 64,500	86,000 86,000	92,400 93,600						
39	43,000	64,500	86,000	94,800						
40	43,000 43,000	64,500 64,500	86,000 86,000	96,000 97,200						
42	43,000 43,000	64,500 64,500	86,000 86,000	98,400 99,600						
44 45	43,000 43,000	64,500 64,500	86,000 86,000	100,800 102,000						
46 47	43,000 43,000	64,500 64,500	86,000 86,000	103,200 104,400						
48 49	43,000 43,000	64,500 64,500	86,000 86,000	105,600 106,800	400 000	*	_			
50 51	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	108,000 109,200		Formulas ap	oplied:		
52 53	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	110,400 111,600	; (1)			se in feet plus	40) when
54 55	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	112,800 114,000	11 18		s 18 feet or le (the wheelba	ss. se in feet plus	40) when
56 57	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	115,200 116,400			s more than 1		,
58 59	<b>43,000</b> 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	117,600 118,800	*				
60 61	<b>43,000</b> 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	120,000 121,200					
<b>62</b> 63	<b>43,000</b> 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	<b>107,500</b> 107,500	122,400 123,600					
<b>64</b> 65	<b>43,000</b> 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	124,800 126,000					
<b>66</b>	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	127,200 128,400		·			
<b>68</b> 69	43,000 43,000	<b>64,500</b> <b>64,500</b>	86,000 86,000	107,500 107,500	129,000 129,000	129,600 130,800				
70 71	43,000 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	132,000 133,200				
72 73	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	134,400 135,600				
74	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	136,800 138,000				
75 Distance measu							ahan		FORM 735-8112 (3	14) CTV# 200EE0

WHEEL BASE	2 Axles	3 Axles	4 Axies	5 Axies	6 Axles	7 Axles	8 Axles	9 Axles	10 Axles	11 Axles or more
76	43,000	64,500	86,000	107,500	129,000	139,200	Axies	Axies	Axies	OI IIIOIE
77	43,000	64,500	86,000	107,500	129,000	140,400	==			
78 79	<b>43,000</b> 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	141,600 142,800				
80	43,000	64,500	86,000	107,500	129,000	144,000				
81	43,000	64,500	86,000	107,500	129,000	145,200				
<b>82</b> 83	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	146,400 147,600				
84	43,000	64,500	86,000	107,500	129,000	148,800				
85 86	43,000	64,500	86,000	107,500	129,000	150,000	4-4 000			
87	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	151,200 152,400			
88	43,000	64,500	86,000	107,500	129,000	150,500	153,600			
89 90	43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 <b>107,500</b>	129,000 129,000	150,500	154,800			
91	<b>43,000</b> 43,000	64,500	86,000	107,500	129,000	150,500 150,500	156,000 157,200			
92	43,000	64,500	86,000	107,500	129,000	150,500	158,400			
93	43,000	64,500	86,000	107,500	129,000	150,500	159,600			
94 95	<b>43,000</b> 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	160,800 162,000			
96	43,000	64,500	86,000	107,500	129,000	150,500	163,200			
97	43,000	64,500	86,000	107,500	129,000	150,500	164,400			
98 99	43,000 43,000	<b>64,500</b> 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	165,600 166,800			
100	43,000	64,500	86,000	107,500	129,000	150,500	168,000			
101	43,000	64,500	86,000	107,500	129,000	150,500	169,200			
102 103	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	170,400 171,600			
104	43,000	64,500	86,000	107,500	129,000	150,500	172,000	172,800		
105	43,000	64,500	86,000	107,500	129,000	150,500	172,000	174,000	2774	
106 107	<b>43,000</b> <b>43,000</b>	64,500 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	175,200 176,400		
108	43,000	64,500	86,000	107,500	129,000	150,500	172,000	177,600		
109	43,000	64,500	86,000	107,500	129,000	150,500	172,000	178,800	20	
110 111	43,000 43,000	64,500 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	1 <b>72,000</b> 172,000	180,000 181,200		
112	43,000	64,500	86,000	107,500	129,000	150,500	172,000	182,400		
113	43,000	64,500	86,000	107,500	129,000	150,500	172,000	183,600		
114 115	43,000 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	184,800 186,000		
116	43,000	64,500	86,000	107,500	129,000	150,500	172,000	187,200		
117	43,000	64,500	86,000	107,500	129,000	150,500	172,000	188,400	***	
118 119	43,000 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	189,600 190,800		
120	43,000	64,500	86,000	107,500	129,000	150,500	172,000	192,000		
121	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,200		
122 123	43,000 43,000	<b>64,500</b> 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	194,400 195,600	
124	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	196,800	
125	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	198,000	
126 127	43,000 43,000	64,500 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	199,200 200,400	
128	43,000 43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	201,600	
129	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	202,800	
130 131	<b>43,000</b> 43,000	<b>64,500</b> 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	204,000 205,200	
132	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	206,400	
133	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	207,600	
134 135	43,000	<b>64,500</b> 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	208,800 210,000	
136	43,000 43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	211,200	
137	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	212,400	
138	43,000	64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	213,600 214,800	
139 140	43,000 <b>43,00</b> 0	64,500 <b>64,500</b>	86,000	107,500	129,000	150,500	172,000	193,500	215,000	216,000
141	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	217,200
142	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000 215,000	218,400 219,600
143 144	43,000 <b>43,000</b>	64,500 <b>64,500</b>	86,000 <b>86,00</b> 0	107,500 107,500	129,000 1 <b>29,00</b> 0	150,500 <b>150,50</b> 0	172,000 1 <b>72,00</b> 0	193,500 <b>193,50</b> 0	215,000	219,600
145	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	222,000
146	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	223,200
147 148	43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 <b>107,500</b>	129,000 129,000	150,500 150,500	172,000 172,000	193,500 1 <b>93,500</b>	215,000 215,000	224,400 225,600
148	43,000 43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	226,800
150	43,000	64,500	86,000	107,500	129,000	150,500 next larger nur	172,000	193,500	215,000 PERMIT WEIGHT TA	228,000



OREGON DEPARTMENT OF TRANSPORTATION MOTOR CARRIER TRANSPORTATION DIVISION OVER-DIMENSION PERMIT UNIT 3930 FAIRVIEW INDUSTRIAL DRIVE SE SALEM OREGON 97302-1166

## **Permit Weight Table 4**

**REVISED 03-2014** 

WHEEL BASE	2 Axles	3 Axies	4 Axies	5 Axles	6 Axles	7 Axles	8 Axles	9 Axles	10 Axles	11 Axies	12 Axles	13 Axles	14 Axles	15 Axles or more
5	43,000 43,000				•									
6 7	43,000 43,000													
8 OVER 8'	] 43,000 (BUT LESS 1	ΓHAN 8'6")												
9	43,000 43,000	57,600 58,800								group o				
10	43,000	64,500 64,500	65,000 68,200						ill not ex the follo	ceed tha wing:	t specifie	ed in this	permit	weight
12	43,000 43,000	64,500	70,400				iabic C	rany or	the folio	mng.				
13 14	43,000 43,000	64,500 64,500	72,600 <b>74,800</b>							urer's sia				to
15 16	43,000 43,000	64,500 64,500	77,000 <b>79,200</b>							ounds pe s per sin		tire wia	m;	Comments of the
17 18	43,000 43,000	64,500 <b>64,500</b>	81,400 <b>83,600</b>					43,00	<b>0</b> pound:	s per tan	dem axl			
19 20	43,000 43,000	64,500 64,500	85,800 <b>86,000</b>	88,000						own on t			m avla i	25
21	43,000	64,500	86,000	90,200						e permitt ight, whi			ii axie, t	ונ
22 23	43,000 43,000	<b>64,500</b> <b>64,500</b>	<b>86,000</b> 86,000	<b>92,400</b> 94,600						described			2-0010 (	(2)
24 25	43,000 43,000	<b>64,500</b> 64,500	86,000 86,000	96,800 99,000										
26 27	<b>43,000</b> 43,000	<b>64,500</b> 64,500	86,000 86,000	101,200 103,400										
<b>28</b> 29	43,000 43,000	<b>64,500</b> 64,500	86,000 86,000	105,600 107,500	107,800									
30 31	43,000	<b>64,500</b> 64,500	86,000 86,000	107,500 107,500	110,000 113,600									
32	43,000 43,000	64,500	86,000	107,500	115,200									
33 34	43,000 <b>43,000</b>	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 <b>107,500</b>	116,800 118,400									
35 36	43,000 43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 <b>107,500</b>	120,000 <b>121,600</b>									
37 38	43,000 43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 107,500	123,200 124,800									
39 40	43,000 43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 107,500	126,400 128,000									
41	43,000	64,500	86,000	107,500	129,000	129,600								
42 43	<b>43,000</b> 43,000	64,500 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	131,200 132,800	Si							Taxan Cara
44 45	43,000 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	134,400 136,000								[
46 47	<b>43,000</b> <b>43,000</b>	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	137,600 139,200								
<b>48</b> 49	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	140,800 142,400								
50	43,000	64,500	86,000 86,000	107,500	129,000	144,000 145,600								
51 52	43,000 43,000	64,500 64,500	86,000	107,500 107,500	129,000	147,200								
53 54	43,000 43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 107,500	129,000 129,000	148,800 150,400				g55030000000000000000000000000000000000				
55 <b>56</b>	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	152,000 153,600			Forwein	hts beyon	d 15 avlad	and 150	feet of
57 58	43,000 <b>43,00</b> 0	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 107,500	129,000 129,000	150,500 150,500	155,200 1 <b>56,80</b> 0				se, apply i			
59 <b>60</b>	43,000 43,000	64,500 <b>64,500</b>	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	158,400 160,000			4 000 11		.t		a 40)
61	43,000	64,500	86,000	107,500	129,000	150,500	161,600 163,200	1			nes (the w neelbase is			8 40)
<b>62</b> 63	<b>43,000</b> 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	164,800							
<b>64</b> 65	43,000 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	166,400 168,000							
<b>66</b> 67	<b>43,000</b> 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	169,600 171,200							APPROPRIENT
68	43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	172,800 174,400						
69 70	43,000 <b>43,000</b>	64,500	86,000	107,500	129,000	150,500	172,000	176,000						
71 72	43,000 <b>43,000</b>	64,500 <b>64,500</b>	86,000 <b>86,00</b> 0	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	177,600 <b>179,20</b> 0						-
73 74	43,000 43,000	64,500 64,500	86,000 86,000	107,500 <b>107,500</b>	129,000 129,000	150,500 150,500	172,000 172,000	180,800 182,400						
75	43,000	64,500	86,000	107,500	129,000	150,500	172,000	184,000	m mumban					STK# 300560

WHEEL BASE	2 Axles	3 Axles	4 Axles	5 Axles	6 Axles	7 Axles	8 Axles	9 Axles	10 Axles	11 Axles	12 Axles	13 Axles	14 Axles	15 Axles or more
76	43,000	64,500	86,000	107,500	129,000	150,500	172,000	185,600	Axies		Axies	Axies	Axies	
77	43,000	64,500	86,000	107,500	129,000	150,500	172,000	187,200	·					
78 79	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	188,800 190,400	i					
80	43,000	64,500	86,000	107,500	129,000	150,500	172,000	192,000						
81 82	43,000 <b>43,000</b>	64,500 64,500	86,000 <b>86,000</b>	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	193,600 195,200					
83	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	196,800					
84 85	43,000	64,500	<b>86,000</b> 86,000	107,500	129,000	150,500	172,000	193,500	198,400					
86	43,000 43,000	64,500 <b>64,500</b>	86,000	107,500 <b>107,500</b>	129,000 129,000	150,500 150,500	172,000 1 <b>72,000</b>	193,500 193,500	200,000 <b>201,600</b>					
87	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	203,200					
<b>88</b> 89	43,000 43,000	<b>64,500</b> 64,500	<b>86,000</b> 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	204,800 206,400					
90	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	208,000					
91 92	43,000 43,000	64,500 <b>64,500</b>	86,000 86,000	107,500 <b>107,500</b>	129,000 129,000	150,500 <b>150,500</b>	172,000 172,000	193,500 193,500	209,600 211,200					
93	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	212,800					
94	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	214,400	040.000				
95 96	43,000 43,000	64,500 <b>64,500</b>	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000 215,000	216,000 217,600				
97	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	219,200	:			
98	43,000 43,000	<b>64,500</b> 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000	220,800 222,400				
100	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000 215,000	224,000				
101	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	225,600				
102	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000 215,000	227,200 228,800				
104	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	230,400				
105 106	43,000 43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 107,500	129,000 1 <b>29,00</b> 0	150,500 <b>150,500</b>	172,000 172,000	193,500 193,500	215,000 215,000	232,000 233,600				
107	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	235,200				
108	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	236,800			
109 110	43,000 <b>43,000</b>	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 1 <b>72,00</b> 0	193,500 193,500	215,000 215,000	236,500 236,500	238,400 <b>240,000</b>			
111	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	241,600			
112 113	<b>43,000</b> <b>43,000</b>	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000 215,000	236,500 236,500	243,200 244,800			
114	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	246,400			
115	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	248,000			
116 117	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000 215,000	236,500 236,500	249,600 251,200			
118	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	252,800			
119 120	43,000 43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000 215,000	236,500 236,500	254,400 256,000			
121	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	257,600			
122	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	259,200		
123 124	43,000 43,000	64,500 64,500	86,000 <b>86,000</b>	107,500	129,000 1 <b>29,00</b> 0	150,500 150,500	172,000 1 <b>72,000</b>	193,500 1 <b>93,500</b>	215,000 215,000	236,500 236,500	258,000 258,000	260,800 262,400		
125	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	264,000		
126 127	43,000 43,000	<b>64,500</b> 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000 215,000	236,500 236,500	258,000 258,000	265,600 267,200		
128	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	268,800		e de la companya de l
129	43,000	64,500	86,000	107,500 107,500	129,000 1 <b>29,000</b>	150,500 150,500	172,000 172,000	193,500	215,000	236,500 236,500	258,000 258,000	270,400 <b>272,000</b>		
130	43,000 43,000	64,500 64,500	<b>86,000</b> 86,000	107,500	129,000	150,500	172,000	193,500 193,500	215,000 215,000	236,500	258,000	273,600		
132	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	275,200		
133 134	43,000 43,000	64,500 <b>64,500</b>	86,000 <b>86,000</b>	107,500 107,500	129,000 129,000	150,500 150,500	172,000 1 <b>72,000</b>	193,500 193,500	215,000 215,000	236,500 <b>236,500</b>	258,000 258,000	276,800 <b>278,400</b>		
135	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	279,500	280,000	
136	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	279,500 279,500	281,600 283,200	
137 138	43,000 43,000	64,500 64,500	86,000 <b>86,000</b>	107,500 <b>107,500</b>	129,000 1 <b>29,000</b>	150,500 <b>150,500</b>	172,000 172,000	193,500 193,500	215,000 215,000	236,500 236,500	258,000 <b>258,0</b> 00	279,500	284,800	
139	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	279,500	286,400	}
140 141	43,000 43,000	<b>64,500</b> 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000 215,000	236,500 236,500	258,000 258,000	279,500 279,500	288,000 289,600	
142	43,000 43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	279,500	291,200	
143	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	279,500 279,500	292,800 294,400	
144 145	43,000 43,000	64,500 64,500	86,000 86,000	107,500 107,500	129,000 129,000	150,500 150,500	172,000 172,000	193,500 193,500	215,000 215,000	236,500 236,500	258,000 258,000	279,500	296,000	
146	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	279,500	297,600	
147	43,000	64,500	86,000 <b>86,000</b>	107,500 107,500	129,000 129,000	150,500 <b>150,500</b>	172,000 172,000	193,500 193,500	215,000 215,000	236,500 236,500	258,000 258,000	279,500 279,500	299,200 <b>300,800</b>	
148 149	43,000 43,000	<b>64,500</b> 64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	279,500	301,000	302,400
150	43,000	64,500	86,000	107,500	129,000	150,500	172,000	193,500	215,000	236,500	258,000	279,500	301,000	304,000

## OREGON DEPARTMENT OF TRANSPORTATION MOTOR CARRIER TRANSPORTATION DIVISION 550 CAPITOL ST NE SALEM OR 97301-2530

### **PERMIT WEIGHT TABLE**

5

WH	ELBASE		•																
	2	3	4	5	6	.7	8	9	10	11	12	13	14	15	16	17	18	19	20
	Axles	Axles	Axles	Axles	Axles	Axles	Axica	Axles	Axles		Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axles
4			43,000					•			43,000				-		•		-
6			43,000	43,000 43,000						<del></del>	43,000			43,000	43,000 43,000				43,000
7			43,000									•		43,000	43,000		-		43,000
8			43,000		43,000	43,000	43,000	43,000	43,000	43,000	43,000	43,000	43,000	43,000	43,000	43,000	43,000	43,000	43,000
c	VER 8' (B				E0 000	En 000	= 0.000	E0 000	En 000	E0 000	En 000	E0 000	E0 000	E0 000	F0 000	F0 000	F0 000	F0 000	
9			52,000 58,500	52,000 58,500	•						52,000 58,500	52,000 58,500		52,000 58,500	52,000 58,500	52,000 58,500	•	•	52,000 58,500
10		65,000		65,000			-	-		-	65,000	65,000		65,000	65,000	65,000			65,000
11	43,000	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200	68,200
12		70,400		70,400			-	-			70,400	70,400		70,400	70,400	70,400	-		70,400
13	•			72,600 74,800	•	•		72,600 74,800	•		72,600 74,800	72,600 74,800	•	72,600 74,800	72,600 74,800	72,600 74,800		72,600 74,800	72,600 74.800
15				77,000	-					-	77,000	77,000	77,000	77,000	77,000	77,000	77,000	,	
16	43,000	72,000	79,200	79,200	79,200	79,200	-		79,200	79,200	79,200	79,200	79,200	79,200	79,200	79,200	79,200	79,200	79,200
17	43,000	-		81,400							81,400	81,400	81,400	81,400	81,400	81,400	81,400	81,400	81,400
18	•			83,600 85,800				83,600 85,800			83,600 85,800	83,600 . 85,800	83,600 85,800						
20	43,000			88,000	88,000			88,000	•		88,000	88,000	88,000	88,000	88,000	88,000	88,000	88,000	88,000
21	43,000			90,200	90,200			90,200			90,200	90,200	90,200	90,200	90,200	90,200	90,200	90,200	
22	-			92,400	92,400 94,600	-		92,400		92,400	92,400 94,600	92,400	92,400	92,400	92,400	92,400	92,400	92,400	92,400
23 24	43,000 43,000		•	94,600 96,800	94,600 96,800			94,600 96,800			94,600 96,800	94,600 96,800	94,600 96,800	94,600 96,800	94,600 96,800	94,600 96,800	94,600 96,800		94,600 96,800
25	43,000			99,000			-	99,000			99,000	-	99,000	99,000	99,000	99,000	•	99,000	99,000
26			-							101,200									
27					-	-	-		-	103,400		-	•	•	•		-	-	
28 29		-								105,600 107,800									
30										110,000									
31										113,600									
32										115,200									
33										116,800 118,400									
34 35		-								120,000									
36	43,000	72,000	96,000	120,000	121,600	121,600	121,600	121,600	121,600	121,600	121,600	121,600	121,600	121,600	121,600	121,600	121,600	121,600	121,600
37	•									123,200									
38										124,800 126,400									
40		-								128,000									
41							129,600								<del></del>		129,600		
42					-					131,200									
43		- 1								132,800 134,400									
44	-									136,000									
46										137,600									
47										139,200									
48										140,800 142,400									
49 50	43,000																		
51										145,600									
1	43,000																		
	43,000																		
	43,000 43,000																		
	43,000																		
57	43,000	72,000	96,000	120,000	144,000	155,200	155,200	155,200	155,200	155,200	155,200	155,200	155,200	155,200	155,200	155,200	155,200	155,200	155,200
	43,000																		
	43,000 °																		
	43,000																		
	43,000																		
63	43,000	72,000	96,000	120,000	144,000	164,800	164,800	164,800	164,800	164,800	164,800	164,800	164,800	164,800	164,800	164,800	164,800	164,800	164,800
	43,000																		
	43,000					···													
1	43,000 7																		
	43,000	-															-		-
1	43,000																		
70	43,000 7	72,000 9	96,000	120,000	144,000	168,000	176,000	176,000	176,000	176,000	176,000	176,000	176,000	176,000	176,000	176,000	176,000	176,000	176,000

<u> </u>																				
WH	EEL	BASE	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	. 19	20
	А	xles	Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axles	Axies	Axles	Axles	Axics	Axles
7	1 43	3,000	72,000	96,000	120,000	144,000	168,000	177,600	177,600	177,600	177,600	177,600	177,600	177,600	177,600	177,600	177,600	177,600	177,600	177,600
7	2 43	3,000	72,000	96,000	120,000	144,000	168,000	179,200	179,200	179,200	179,200	179,200	179,200	179,200	179,200	179,200	179,200	179,200	179,200	179,200
7	3 43	000,	72,000	96,000	120,000	144,000	168,000	180,800	180,800	180,800	180,800	180,800	190,800	190,800	100,000	100,000	199,400	180,800 182,400	199.400	190,000
7	4 43	3,000	72,000	96,000	120,000	144,000	168,000	184 000	184 000	184,000	184.000	-162,400 -184.000	184,000	184.000	184.000	184,000	184,000	184,000	184.000	184.000
1 7	6 43	2,000	72,000	96,000	120,000	144,000	168.000	185,600	185,600	185,600	185,600	185,600	185,600	185,600	185,600	185,600	185,600	185,600	185,600	185,600
7	7 43	3,000	72,000	96,000	120,000	144,000	168,000	187,200	187,200	187,200	187,200	187,200	187,200	187,200	187,200	187,200	187,200	187,200	187,200	187,200
																		188,800		
																		190,400		
																		192,000		
																		193,600 195,200		
																		196,800		
																		198,400		
																		200,000		
																		201,600		
																		203,200		
																		204,800		
																		206,400		
																		208,000		
																		209,600		
																		211,200 212,800		
																		214,400		
																		216,000		
																		217,600		
9	7 43	3,000	72,000	96,000	120,000	144,000	168,000	192,000	216,000	219,200	219,200	219,200	219,200	219,200	219,200	219,200	219,200	219,200	219,200	219,200
																		220,800		
																		222,400		
																		224,000 225,600		
																		227,200		
																		228,800		
																		230,400		
																		232,000		
																		233,600		
10	7 43	,000	72,000	96,000	120,000	144,000	168,000	192,000	216,000	235,200	235,200	235,200	235,200	235,200	235,200	235,200	235,200	235,200	235,200	235,200
																		236,800		
																		238,400		
																		240,000		
																		241,600		
																		243,200 244,800		
																		246,400		
																		248,000		
																		249,600		
																		251,200		
																		252,800		
11:	9 43	,000	72,000	96,000	120,000	144,000	168,000	192,000	216,000	240,000	254,400	254,400	254,400	254,400	254,400	254,400	254,400	254,400	254,400	254,400
																		256,000		
																		257,600		
																		259,200 : 260,800 :		
																		262,400		
																		264,000		
																		265,600		
																		267,200		
12	3 43	,000 :	72,000	96,000	120,000	144,000	168,000	192,000	216,000	240,000	264,000	268,800	268,800	268,800	268,800	268,800	268,800	268,800	268,800	268,800
																		270,400		
																		272,000		
																		273,600 :		
																		275,200 :		
																		276,800 : 278,400 :		
																		280,000 S		
																		281,600		
137	7 43	,000	72,000	96,000	120,000	144,000	168,000	192,000	216,000	240,000	264,000	283,200	283,200	283,200	283,200	283,200	283,200	283,200	283,200	283,200
138	3 43	,000	72,000	96,000	120,000	144,000	168,000	192,000	216,000	240,000	264,000	284,800	284,800	284,800	284,800	284,800	284,800	284,800	284,800	284,800
139	43,	,000	72,000	96,000	120,000	144,000	168,000	192,000	216,000	240,000	264,000	286,400	286,400	286,400	286,400	286,400	286,400	286,400	286,400	286,400
140	43	,000 7	72,000	96,000	120,000	144,000	168,000	192,000	216,000	240,000	264,000	288,000	288,000	288,000	288,000	288,000	288,000	288,000	288,000	288,000
																		289,600		
																		291,200		
																		292,800 :		
		•																294,400		
																		296,000 2		
																		297,600 2 299,200 2		
																		300,800 3		
																		302,400		
4																		304,000		:
1	-,	•				-	*													i

